



(U) mit / with UL-Recognition US

Type	Größe / size	Abmessungen / dimensions														max. Gewicht / weight	
		A	B	C	D	E	F	G	H	J	K	L	M	N	P		Q
	AxC																
GLAD(U)	100x34	100	50	34	13	3	9	1,9	88	4,5	10	27	15	6	5,7	8,2	140
GLAD(U)	180x34	180	50	34	13	3	9	1,9	168	4,5	10	27	15	6	5,7	8,2	230
GLAD(U)	207x34	207	50	34	13	3	9	1,9	195	4,5	10	27	15	6	5,7	8,2	250
GLAD(U)	230x34	230	50	34	13	3	9	1,9	218	4,5	10	27	15	6	5,7	8,2	270

Schutzart IP 40 Degree of protection IP 40		Allgemeintoleranz ISO 2768-m		Maßstab : Werkstoff :		Gew.	
8				Datum	Name	Gekapselter Widerstand Enclosed resistor Type GLAD(U) ... x 34	
7				Bearb. 14.11.06	Lutz		
6				Gepr. 25.07.18	Gg		
5				Norm			
4	Div. Änderungen	24.07.18	Ke				
3	Pos. Leitungen	24.06.10	DT	<b>FRIZLEN</b> D-71712 MURR		<b>13 M 0573</b>	Blatt
2	Typen hinzu.	15.03.10	Pierri				
1	Langloch + Maße	03.08.07	Lutz				
Zust	Änderung	Datum	Name	Ers. f.:	Ers. d.:		

